

## Straight Liquidtight Connectors-Zinc Die Cast

**•Application:**

These straight connectors are used on flexible metallic liquid-tight conduits and Type-B flexible, nonmetallic, liquidtight conduits. They are used to positively bond conduits to boxes or enclosures in both wet and damp locations.

**•Material:** Zinc die cast



Non-Insulated



Insulated

Non-Insulated Catalog Number	Insulated Catalog Number	Trade Size	Inner Pack	Master Pack
ZQLTCNZ-38	ZQLTCNZ-38I	3/8"	20	200
ZQLTCNZ-50	ZQLTCNZ-50I	1/2"	20	200
ZQLTCNZ-75	ZQLTCNZ-75I	3/4"	10	100
ZQLTCNZ-100	ZQLTCNZ-100I	1"	5	50
ZQLTCNZ-125	ZQLTCNZ-125I	1- 1/4"	5	50
ZQLTCNZ-150	ZQLTCNZ-150I	1- 1/2"	/	20
ZQLTCNZ-200	ZQLTCNZ-200I	2"	/	20
ZQLTCNZ-250	ZQLTCNZ-250I	2- 1/2"	/	1
ZQLTCNZ-300	ZQLTCNZ-300I	3"	/	1
ZQLTCNZ-400	ZQLTCNZ-400I	4"	/	1